

EP50

Servo-motorized CNC Axial Powder Press for Highest Demands on Productivity and Parts Quality



Advantages

- High precision and productivity
- Very precise closed-loop position control
- High-resolution closed-loop force control
- Intuitive operation
- Low energy consumption
- Installation at ground level without pit
- Compatible with DORST IoT Solutions

Technical information

- Pressing force: 500 kN
- Upper punch travel: 250 mm
- Holding pressure of die: 180 kN
- Withdrawal force of die: 180 kN
- Filling height: 130 mm
- Core rod travel: 100 mm
- Positioning accuracy of main drives: ±0,001 mm

Keyfacts

- Highly dynamic axis drives
- Precision force measurement
- Precise closed-loop force control
- Closed-loop controlled upper punch hold-down
- Quick tool change
- Intuitive programming and operation
- Very low noise emission
- Intelligent energy management system
- Low carbon footprint
- TCO optimized



Characteristics

- Backlash-free crosshead guide
- Servo-motorized closed-loop controlled core rod
- Servo-motorized closed-loop controlled filler axis
- Max. 3 filler axes
- Low maintenance
- Installation at ground level
- Ergonomic design

Technologies

- Withdrawal process
- Quick-action tool clamping systems
- IPG® support
- DTS DORST Tool Setup
- Automation systems
- Multi-material filling technology
- Network-compatible
- DORST IoT Solutions